

LV CONTROL, MULTI CORE, SCREENED, UNARMoured CABLE AS PER IEC 60502-1 (CU/XLPE/PVC/CUT/PVC)

APPLICATION

Suitable for indoor Motor Control, power distribution, low-voltage installations, lighting circuits, and low-risk environments where mechanical protection is not critical. Ideal for use in conduits, trunking, and in locations protected from physical damage.

CONSTRUCTION

Conductor:	Stranded (Class 2) Annealed Plain Copper Conductor to IEC 60228.
Insulation:	Cross linked polyethylene (XLPE)
Insulation Color:	2C:- Red & Black 3C:- Red, Yellow & Blue 4C:- Red, Yellow, Blue & Black 5C & above:- Black core with number printed Other colors are available upon request.
Laying Up:	Cores are assembled in concentric layers and laid up with a non-hygroscopic filler (if required), and the assembly is wrapped with binder tape.
Inner Sheath:	Extruded layer of Polyvinyl Chloride (PVC) consistent with the operating temperature of the cable in Black colour. Other colors are available upon request.
Metallic Screen:	The screen shall consist of copper tape (50µm) applied helically over the inner covering for 100% coverage and with a suitable overlap. Copper tape with 75µm, 100µm are also available on request.
Outer Sheath:	Extruded Polyvinyl Chloride (PVC) Type ST-2 to IEC 60502-1 in Black color. Other colors are available upon request.
Marking Text on the Outer Sheath (Example):	CU/XLPE/PVC/CUT/PVC (NO. OF CORES X CONDUCTOR SIZE) 600/1000V IEC 60502-1 TEKAB YEAR OF MANUFACTURE MADE IN UAE LENGTH METER MARKING



TECHNICAL DATA

Operating Temperature:	During Normal Operation - 90°C During Short Circuit Condition - 250°C
Voltage Rating:	600/1000V
Voltage Withstand:	3500 V a.c. r.m.s. for 5 minutes

*Other special sheath materials are also available with Flame Retardant :- IEC 60332-1-2, IEC 60332-3-22 (CAT A), IEC 60332-3-24 (CAT C), Low Smoke, UV / Sunlight Resistant, Oil Resistant, Anti-Termite, Anti-Rodent.

Circular Conductor:-

SERIAL NO.	TEKAB CODE	NO. OF CORES X CONDUCTOR SIZE (NO. X Sq.mm.)	NO. OF STRANDS	NOMINAL INSULATION THICKNESS (mm)	NOMINAL INNER SHEATH THICKNESS (mm)	METALLIC SCREEN THICKNESS (mm)	NOMINAL OUTER SHEATH THICKNESS (mm)	APPROX. OVERALL DIAMETER (mm)	APPROX. WEIGHT (kg/km)
1	XVC7V	2C X 1.5	7	0.7	1.0	0.05	1.8	12.0	200
2	XVC7V	3C X 1.5	7	0.7	1.0	0.05	1.8	12.5	225
3	XVC7V	4C X 1.5	7	0.7	1.0	0.05	1.8	13.0	260
4	XVC7V	5C X 1.5	7	0.7	1.0	0.05	1.8	14.0	300
5	XVC7V	6C X 1.5	7	0.7	1.0	0.05	1.8	15.0	350
6	XVC7V	7C X 1.5	7	0.7	1.0	0.05	1.8	15.0	365
7	XVC7V	8C X 1.5	7	0.7	1.0	0.05	1.8	15.5	385
8	XVC7V	10C X 1.5	7	0.7	1.0	0.05	1.8	17.0	450
9	XVC7V	12C X 1.5	7	0.7	1.0	0.05	1.8	18.0	500
10	XVC7V	14C X 1.5	7	0.7	1.0	0.05	1.8	18.5	550
11	XVC7V	15C X 1.5	7	0.7	1.0	0.05	1.8	19.0	600
12	XVC7V	16C X 1.5	7	0.7	1.0	0.05	1.8	19.5	625
13	XVC7V	18C X 1.5	7	0.7	1.0	0.05	1.8	20.5	675
14	XVC7V	19C X 1.5	7	0.7	1.0	0.05	1.8	21.0	700
15	XVC7V	20C X 1.5	7	0.7	1.0	0.05	1.8	21.2	725
16	XVC7V	22C X 1.5	7	0.7	1.0	0.05	1.8	22.0	775
17	XVC7V	24C X 1.5	7	0.7	1.0	0.05	1.8	22.5	825
18	XVC7V	25C X 1.5	7	0.7	1.0	0.05	1.8	23.0	850
19	XVC7V	26C X 1.5	7	0.7	1.0	0.05	1.8	23.5	875
20	XVC7V	30C X 1.5	7	0.7	1.0	0.05	1.8	24.5	975
21	XVC7V	32C X 1.5	7	0.7	1.0	0.05	1.8	25.5	1050
22	XVC7V	35C X 1.5	7	0.7	1.0	0.05	1.8	26.0	1125
23	XVC7V	36C X 1.5	7	0.7	1.0	0.05	1.8	26.5	1150
24	XVC7V	40C X 1.5	7	0.7	1.0	0.05	1.8	27.5	1225
25	XVC7V	50C X 1.5	7	0.7	1.0	0.05	1.8	30.0	1475
26	XVC7V	61C X 1.5	7	0.7	1.0	0.05	1.8	32.5	1750

SERIAL NO.	TEKAB CODE	NO. OF CORES X CONDUCTOR SIZE (NO. X Sq.mm.)	NO. OF STRANDS	NOMINAL INSULATION THICKNESS (mm)	NOMINAL INNER SHEATH THICKNESS (mm)	METALLIC SCREEN THICKNESS (mm)	NOMINAL OUTER SHEATH THICKNESS (mm)	APPROX. OVERALL DIAMETER (mm)	APPROX. WEIGHT (kg/km)
27	XVC7V	2C X 2.5	7	0.7	1.0	0.05	1.9	12.5	225
28	XVC7V	3C X 2.5	7	0.7	1.0	0.05	1.8	13.2	275
29	XVC7V	4C X 2.5	7	0.7	1.0	0.05	1.8	14.0	325
30	XVC7V	5C X 2.5	7	0.7	1.0	0.05	1.8	15.0	375
31	XVC7V	6C X 2.5	7	0.7	1.0	0.05	1.8	16.0	425
32	XVC7V	7C X 2.5	7	0.7	1.0	0.05	1.8	16.0	435
33	XVC7V	8C X 2.5	7	0.7	1.0	0.05	1.8	17.0	480
34	XVC7V	10C X 2.5	7	0.7	1.0	0.05	1.8	18.5	575
35	XVC7V	12C X 2.5	7	0.7	1.0	0.05	1.8	19.5	650
36	XVC7V	14C X 2.5	7	0.7	1.0	0.05	1.8	20.5	725
37	XVC7V	15C X 2.5	7	0.7	1.0	0.05	1.8	21.0	775
38	XVC7V	16C X 2.5	7	0.7	1.0	0.05	1.8	21.5	800
39	XVC7V	18C X 2.5	7	0.7	1.0	0.05	1.8	22.5	900
40	XVC7V	19C X 2.5	7	0.7	1.0	0.05	1.8	23.0	925
41	XVC7V	20C X 2.5	7	0.7	1.0	0.05	1.8	23.5	950
42	XVC7V	22C X 2.5	7	0.7	1.0	0.05	1.8	24.2	1025
43	XVC7V	24C X 2.5	7	0.7	1.0	0.05	1.8	25.0	1100
44	XVC7V	25C X 2.5	7	0.7	1.0	0.05	1.8	25.5	1150
45	XVC7V	26C X 2.5	7	0.7	1.0	0.05	1.8	25.8	1175
46	XVC7V	30C X 2.5	7	0.7	1.0	0.05	1.8	27.5	1325
47	XVC7V	32C X 2.5	7	0.7	1.0	0.05	1.8	28.0	1400
48	XVC7V	35C X 2.5	7	0.7	1.0	0.05	1.8	29.0	1500
49	XVC7V	36C X 2.5	7	0.7	1.0	0.05	1.8	29.5	1550
50	XVC7V	40C X 2.5	7	0.7	1.0	0.05	1.9	31.0	1685
51	XVC7V	50C X 2.5	7	0.7	1.0	0.05	2.0	34.0	2050
52	XVC7V	61C X 2.5	7	0.7	1.0	0.05	2.1	37.0	2450